

NEW DuraTech Adjustable Parts

We have listened to our customers and installers over the past couple years as to how to make DuraTech better and easier to install. We think you will be glad to see these additions and changes. If you have any questions regarding these items please contact your Regional Sales Manager. Information is also available through our Website (www.duravent.com), Customer Service Department and Tech Services Department (800-835-4429).

These new parts are designed to add more adjustability to your installation and to cut back on the number of different part numbers you need in inventory. We have grouped them in 5" & 7" diameters and 6" & 8" diameters. Since the most frequent diameters used are 6" and 8" you may only need to stock the 6DT part numbers.



Adjustable Roof Support
5DT-ARS (5" and 7" Diameters) and 6DT-ARS (6" and 8" Diameters): Designed to support the DuraTech Chimney and allows the chimney to pass through the roof and extend down the ceiling. Ideal for cathedral ceilings and free-standing appliance installations. Supports up to a maximum total chimney length of 45' above and 20' chimney below Roof Support. Adjustable to different roof pitches.

Replaces the 5DT-RS, 6DT-RS, 7DT-RS, and 8DT-RS.
 One part covers 2 diameters (5" & 7" or 6" & 8")



Adjustable Wall Support
5DT-AWS (5" and 7" Diameters) and 6DT-AWS (6" and 8" Diameters): Stabilizes chimney while ensuring a minimum 2" clearance to combustibles. Can adjust out to 6" clearance if needed. One part covers 2 diameters (5" & 7" or 6" & 8").

Replaces 5DT-WS, 6DT-WS, 7DT-WS, 8DT-WS.

Also available in stainless steel: 5DT-AWS-SS, 6DT-AWS-SS.

Replaces 5DT-WSSS, 6DT-WSSS, 7DT-WSSS, 8DT-WSSS.



Adjustable Elbow Strap
5DT-AES (5" and 7" Diameters) and 6DT-AES (6" and 8" Diameters) : Provides required additional support to chimney when using offset elbows.

Replaces 5DT-ES, 6DT-ES, 7DT-ES, 8DT-ES.



NEW PRODUCT
Adjustable Re-Support Bracket
5DT-RES (5" and 7" Diameters) and 6DT-RES (6" & 8" Diameters): Supports up to 20' of DuraTech chimney. Can be installed above or below the tee. Adjustable base slides easily to provide between 2" and 6" of clearance to the wall. Can be used in place of tee support for chimneys under 20'. Or as an addition to tee support that goes beyond 50'.



NEW PRODUCT
Adjustable Extended Wall Support
5DT-XWS (5" and 7" Diameters) and 6DT-XWS (6" & 8" Diameters): Use above the tee to provide support when bypassing obstructions or overhangs. Will support up to 20' of chimney. For 5" diameter, it adjusts from 8 1/2" to 15 1/2". For 6" diameter, it adjusts from 8" to 15". For 7" diameter, it adjusts from 7 1/2" to 14 1/2". For 8" diameter, it adjusts from 7" to 14".

Also available in stainless steel: 5DT-XWS-SS and 6DT-XWS-SS.



Adjustable Extended Roof Bracket
5DT-XRS (5" and 7" Diameters) and 6DT-XRS (6" and 8" Diameters) : Extended roof bracket; provides additional support for the chimney when the chimney extends more than 4' beyond the roof; the legs will extend to handle varying roof slopes. New sandwich clamps allow legs to be extended to any length from 67" to 114". No drilling required.

Replaces 5DT-XRB, 6DT-XRB, 7DT-XRB, 8DT-XRB.