



Keep the purple on the pipe – not on the floor

Get a FREE UV flashlight* RETAIL VALUE: \$200



Inspector can verify the use of Primer with a UV flashlight.

Verify joints have been solvent welded without getting up on a ladder. Oatey All Weather CPVC FlowGuard Gold® with UV indicator and Hercules Un-Purple Primer include properties that glow under ultraviolet light. That means with the right flashlight, you can see that joints have been properly solvent welded. Better yet, Hercules Unpurple Primer goes on clear, leaving no mess on the floor or other surfaces.

MIX & MATCH PROMO!!

1. Buy a total of 4 cases of the products below and receive a UV Flashlight FREE!*
Mix and match to meet your product needs.
2. Simply scan or snap a picture of your receipt and email it to: twulf@stuartassociates.com
3. Be sure to include your name, address and any special shipping instructions.

Offer runs March 15, 2014 through June 15, 2014.

Product Number	Size	Description	Carton Quantity
31918	16 oz	Oatey All Weather 1-step FlowGuard Gold® with Ultraviolet Indicator	24
60447	32 oz	Hercules Un-Purple Primer	12

*Purchase of four cases must be on the same receipt. Allow for one week shipping time. Cannot be delivered to P.O. boxes. Limit three flashlights per contractor. No product substitutions. Offer must be redeemed by August 1, 2014.

FlowGuard Gold® is a registered trademark of The Lubrizol Corporation.



PW-DWV-SW

Meets ASTM F493.

Oatey All Weather 1-step FlowGuard Gold® with Ultraviolet Indicator

- > When applied properly, yellow cement formula glows BLUE under UV light
- > For copper tube size (CTS) CPVC hot and cold potable water and fittings up to 2" diameter, up to 200°F
- > May be used without primer where local codes permit



Hercules Un-Purple Primer

- > Primer appears clear but glows PURPLE under UV light
- > Softens and prepares surface of all schedules of PVC and CPVC pipe and fittings
- > No more purple stains



PW-DWV-SW

Ultraviolet Aluminum Barrel Flashlight

- > C4® LED technology, with a 50,000 hour lifetime. Six 390nm UV LEDs with 100,000 hour lifetime
- > Unbreakable polycarbonate lens
- > Three "C" size alkaline batteries
- > Dimensions: L x W x D: 9.02" x 1.68" x 1.26" (22.9 x 4.26 x 3.2 cm)
- > Weight: 16 oz. (449 g)

RETAIL
VALUE:
\$200



3 lighting modes:
 C4 LED – 3730 candela peak beam intensity,
 185 Lumens, 27 hours runtime
 6 UV LED – 40mW Lumens, 63 hours runtime
 3 UV LED – 30mW Lumens, 81 hours runtime

DISTRIBUTED BY:

OATEYSCS®
Supply Chain Services

216.267.7100 / 800.321.9532
www.oateyscs.com



©2014 Oatey SCS. All Rights Reserved.
This information is based on data believed to be reliable but Oatey makes no warranties, express or implied, as to its accuracy and assumes no liability arising out of its use. The data listed falls within the normal range of product properties but should not be used to establish specification limits or used alone as the basis of design. Oatey's liability to purchasers is expressly limited to the terms and conditions of sale.
Oatey is a trademark of Oatey Co. All other trademarks can be found on www.oatey.com.